

Product information sheet

- Product Name:** Speed Bump (Bumpie), End Cap
- Models:** BMPEC - 2.25" high, weight 5 lbs
BMPEC-AB - 3" high, weight 8 lbs
- Manufacturer:** Clearline Technologies Ltd.
1205 Sherwin Rd, Winnipeg, MB, R3H 0V1
Tel.: +1 (204) 786-3334
Email: engineering@clearline.ca
- Product Specifications:**
1. Material: compression molded composite: 100% recycled rubber and polyurethane prepolymer.
 2. Physical properties of the rubber composite:
 - a) Density 0.6 oz/cu in (ASTM C642)
 - b) Durometer Hardness 70A ± 7 (ASTM D2240)
 - c) Tensile Strength 300 psi (ASTM D412)
 - d) Compression deformation 7% at 70psi, 68°F (ASTM D575)
 - e) Brittleness at Low temperature: -40°F (ASTM D746)
 - f) Freeze and thaw when exposed (ASTM C672)
 - to deicing chemicals no loss after 50 cycles
 - Coefficient of thermal expansion: 8×10^{-5} in/in/°F (ASTM C531)
 4. Dimensions:
 - width 12" (+/- 1/16")
 - length 8.75" (+/- 1/8")
 - thickness 2.25" (+/- 1/8") or thickness 3" (+/- 1/8")
 - weight 5 lbs or 8 lbs
 3. Finishing: Black recycled rubber composite
- Components:**
- a) 100% recycled rubber from car and truck tires (NR, SBR)
 - b) at least 90% of post-consumer materials
 - c) polyurethane prepolymer
- Attached Drawings:** Rubber Speed Bump End Cap 2.25" Thick,
Rubber Speed Bump End Cap 3" Thick,

